

E1 STATIONARY version

Classic model - Ø Maxi 20 mm

- Precise cut with maximum stability and minimum weight
- Capacity : 120 mm² Cu/Al cable
- Weight : 2,9 kg

Code **CCE1S**



For copper, aluminum and multi-fiber cables - NOT SUITABLE FOR STEEL AND STAINLESS STEEL CABLES

E2 STATIONARY version

Classic model - Ø Maxi 31 mm

- Precise cut with maximum stability and minimum weight
- Capacity : 1 x 250 mm² Cu/Al cable
- Dimensions : L 100 x W 110 x H 125 mm
- Weight : 2,9 kg
- Size : 55 cm
- Telecom : 56 x 2 9/10° / U-1000(A)R2V 1 x 300 mm²
- Three-phase underground connection 3 x 50 + 50 mm²

Code **CCE2S**



For copper, aluminum and multi-fiber cables - NOT SUITABLE FOR STEEL AND STAINLESS STEEL CABLES

E3 STATIONARY version

Classic model - Ø Maxi 50 mm

- Precise cut with maximum stability and minimum weight
- Capacity : 500 mm² Cu/Al cable
- Weight : 2,9 kg
- Size : 74 cm
- Tripol twist : 3 x 240 mm² / Aérien 3 x 150 + 70 + 2 x 16 mm²
- U-1000(A)R2V 3 x 185 + 70 mm²

Code **CCE3S**



For copper, aluminum and multi-fiber cables - NOT SUITABLE FOR STEEL AND STAINLESS STEEL CABLES